

► PAS® AirPack 2

Breathing air trolley for airline systems



Technical specifications

PAS® AirPack 2 with 2 pneumatic systems, two hose reels and lifting eye

Size excluding cylinder (H x L x D): 1,140 x 668 x 1,200 mm

Weight: 83.3 kg

Input pressure (high pressure): 200 or 300 bar

Input pressure (medium pressure): 6 to 10 bar

Nominal first stage output pressure: 8 bar

First stage output flow: > 600L/min

High pressure whistle activation pressure: 55 to 60 bar

Medium pressure whistle activation pressure: 4 to 5 bar

Whistle sound level: > 90 dBA

Whistle frequency range: 2,000 to 4,000 Hz

Operating temperature range: from -32 to +70°C

► Accessories



Product description

Designed using the leading technology and materials, the PAS® AirPack 2 is a high capacity breathing air trolley that can contain up to two B50 compressed air cylinders.

► Structure with epoxy coating

The PAS® AirPack 2 airline trolley is made of epoxy anti-static coated steel for use in classified area. The base material is pre-treated to zinc for optimal corrosion protection.

► The Plus pneumatic system

The PAS® AirPack 2 benefits from the internationally renowned, tried and tested, pneumatics system used on Dräger's successful PSS range of compressed air breathing apparatus.

The Plus system incorporates a safety pressure relief valve and the pressure reducer is shrouded in a protective plate for additional safety.

► Compatibility with compressed air cylinders

The PAS® AirPack 2 airline cart is able to accommodate up to two 50 liters compressed air cylinders (*B50 cylinders*). Replacing a cylinder is eased and secured thanks to the exclusive tilting frame.

Designation	Reference
Breathing air trolley, one pneumatic system, one hose reel and lifting eye	33 52 995
Breathing air trolley, two pneumatic systems, two hose reels and lifting eye	33 52 236
50 liters / 300 bar steel cylinder	65 26 395
Y piece for 2 users	R 27 945
5 meter length	AL 01 260
10 meter length	AL 01 261
20 meter length	AL 01 262
30 meter length	33 52 467
50 meter length	33 52 468
PAS F3000P portable filter unit for 3 users with CEJN connectors (1/4" BSP inlet connector)	33 59 916